


Coreless Vibration Motor 4mm / 直流空心杯馬達 4mm

Ø4mm, metal brushes/Ø4mm, 金屬電刷

Outline Drawing/外形圖




Widely used in digital cameras, mobile phones and other electronic products / 廣泛應用於數碼相機, 手機等電子產品

ZXD408 Series / ZXD408系列	Model/型號	001	002	003	004	005	006	007
Motor data (25°C) / 運行參數 (25°C)								
1 Rated voltage/額定電壓	V	1.3	1.5	1.5	3.0	3.0		
2 Range of application/使用範圍	V	1.2-1.8	1.2-1.8	1.2-1.8	2-3.6	2-3.6		
3 Starting voltage/起動電壓	V	0.8	0.8	0.8	1.4	1.4		
4 Rated speed/額定轉速 ±12%	rpm	12,000	12,000	10,000	18,000	15,000		
5 Rated current/額定電流 ≤150%	mA	90	100	100	80	85		
6 Terminal resistance/端電阻 ±20%	Ohm	12.3	12.3	12.3	31.5	31.5		
7 Starting current/起動電流	mA	106	122	122	95	95		
8 Vibrator specifications/振子規格	mA	R2*1.5	R2*2	R1.9*3	R2*2	R2.2*2		
9 Weight of motor/電機重量	g	1.6	1.8	2.1	1.6	1.8		

Additional information/其它相關信息

- Axial play/軸向間隙 0.05~0.30 mm
- Ambient temperature range/環境溫度範圍 -20~+65°C
- Motor parameters can be made according to the request of customer/馬達參數可根據客人要求制作
- Options:Vibrator specifications,connection type/其它可選項: 振子規格,連接方式

Motor typical appearance/馬達典型外觀



Silicon Rubber Case+leadwire/

硅胶套+导线



Silicon Rubber Case+ Metal Dome

硅胶套+弹片



Silicon Rubber Case+ Contactor

硅胶套+触点



Holder+Leadwire

卡夾+導線



Z. X. D Technology Company Limited

Add: Shuibian Industrial Area, Hengli Town, Dongguan City, China

Tel: 86-769-82927257, ext: 611, 613

Website: <http://www.zxd-motor.com>

Fax: 86-769-82927259

Email: jeff@zxd-motor.com